

EXTREME DUTY 7HP MOTOR* BUILT IN WIRELESS REMOTE SYNTHETIC ROPE ALUMINIUM HAWSE FAIRLEAD
OVER-SIZED LOCKING HOOK PATENTED KNURLED & HARDENED DRUM MATTE STEALTH BLACK FINISH
EXTERNALLY MOUNTED BATTERY SWITCH MIL-SPEC BRAIDED BATTERY CABLES LIFETIME WARRANTY

STEALTH

SERIES PERFORMANCE WINCHES



9,000lb 5.5hp

9,000lb 7.0hp

10,000lb 7.0hp

12,000lb 7.0hp

15,000lb 7.0hp

Australian Designed & Tested | Patent #201120104757.7 & 201120104750.5

TJM EQUIPPED
ON AND OFF ROAD. WORK OR PLAY.

STEALTH

SERIES PERFORMANCE WINCHES

While there are endless choices in the off-road winch market today, TJM's approach is one of "over delivering" at an excellent price point. When we started our Stealth project, we brought a clean sheet of paper to the party and mapped out what we believe to be one of the best optioned winch packages in the world today! How did we do it? By owning our own winch factory, why build more of the same? TJM can offer a far superior product, then back it up with legendary service & support, including a lifetime warranty. At TJM we have been keeping people equipped right since 1973 and continue today with the most loyal customer following on the planet!

Starting with a generation 3 contactor pack, we added a huge dose of power swapping in a heavy duty 7.0hp high output motor. Then we put our engineering staff on a common problem "other winch" companies face and came up with our very own solution! A patented knurled & hardened drum, taking the "drum crack warranty" fear out of spooling on our supplied 3/8" Dyneen synthetic rope with massive TJM greaseable self locking hook, all pulled through our very own aluminum hawse fairlead. We didn't stop there though! Every TJM Stealth Series winch has hardened planetary gearing, mil-spec black braided cables, external battery cut-off switch, both wired & wireless real time remote controls! Capped off in our signature Stealth Black finish we've watched so many others try and copy! Let them try.....

Stay Equipped My Friends!

9,000^{lb}
5.5hp

9,000^{lb}
7.0hp

10,000^{lb}
7.0hp

12,000^{lb}
7.0hp

15,000^{lb}
7.0hp



TJM STEALTH WINCH 9000
PN. 160-1305-02-0000

Single line rated pull 9000lbs single-line
Motor 12V 5.5hp, series wound
Control Wired & wireless remote included
Gear Train 3 stage planetary
Gear Reduction Ratio 218:1
Clutch Sliding ring gear
Braking Action Automatic in-the-drum
Drum Diameter/Length 2.5"/8.7"
Synthetic Rope 100ft of 5/16"
Fairlead Polished aluminium hawse fairlead
Battery Recommended 650CCA minimum for winching
Battery Leads 2 gauge
Finish Matte stealth black finish
Weight 70.6lbs
Overall Dimensions 21.9 x 6.3 x 8" (L x W x H)
Mounting Bolt Pattern 10 x 4.5"

FIRST LAYER OF DRUM*

*12volts constant load at winch motor
 *TJM 9K utilizes heavy duty 5.5hp motor

Line Load LBS	Line Speed FPM	Motor Amps
0	24.80	71.00
2000	15.50	135.00
4000	11.50	190.00
6000	9.30	234.00
9000	6.30	334.00

TJM STEALTH WINCH 9000R
PN. 160-1301-01-0000

Single line rated pull 9000lbs single-line
Motor 12V 7.0hp, series wound
Control Wired & wireless remote included
Gear Train 3 stage planetary
Gear Reduction Ratio 130:1
Clutch Sliding ring gear
Braking Action Automatic in-the-drum
Drum Diameter/Length 3"/4.6"
Synthetic Rope 50ft of 5/16"
Fairlead Polished aluminium hawse fairlead
Battery Recommended 650CCA minimum for winching
Battery Leads 2 gauge
Finish Matte stealth black finish
Weight 40lbs
Overall Dimensions 19.25 x 6.75 x 7.5" (L x W x H)
Mounting Bolt Pattern 6.75 x 4.5"

FIRST LAYER OF DRUM*

*12volts constant load at winch motor

Line Load LBS	Line Speed FPM	Motor Amps
0	32.80	68.0
2000	22.05	165.00
4000	19.69	260.00
6000	17.06	340.00
9000	13.12	470.00

TJM STEALTH WINCH 10000
PN. 160-1311-01-0000

Single line rated pull 10000lbs single-line
Motor 12V 7.0hp, series wound
Control Wired & wireless remote included
Gear Train 3 stage planetary
Gear Reduction Ratio 212:1
Clutch Sliding ring gear
Braking Action Automatic in-the-drum
Drum Diameter/Length 3"/7.7"
Synthetic Rope 80ft of 3/8"
Fairlead Polished aluminium hawse fairlead
Battery Recommended 650CCA minimum for winching
Battery Leads 2 gauge
Finish Matte stealth black finish
Weight 60lbs
Overall Dimensions 22.25 x 6.75 x 7.5" (L x W x H)
Mounting Bolt Pattern 10 x 4.5"

FIRST LAYER OF DRUM*

*12volts constant load at winch motor

Line Load LBS	Line Speed FPM	Motor Amps
0	23.60	70.0
2000	15.10	161.00
4000	12.07	220.00
6000	10.50	300.00
8000	9.45	360.00
10000	8.66	405.00

TJM STEALTH WINCH 12000
PN. 160-1321-01-0000

Single line rated pull 12000lbs single-line
Motor 12V 7.0hp, series wound
Control Wired & wireless remote included
Gear Train 3 stage planetary
Gear Reduction Ratio 212:1
Clutch Sliding ring gear
Braking Action Automatic in-the-drum
Drum Diameter/Length 2.5"/8.7"
Synthetic Rope 100ft of 3/8"
Fairlead Polished aluminium hawse fairlead
Battery Recommended 650CCA minimum for winching
Battery Leads 2 gauge
Finish Matte stealth black finish
Weight 60lbs
Overall Dimensions 23.25 x 6.75 x 7.5" (L x W x H)
Mounting Bolt Pattern 10 x 4.5"

FIRST LAYER OF DRUM*

*12volts constant load at winch motor

Line Load LBS	Line Speed FPM	Motor Amps
0	27.00	63.0
2000	15.10	125.00
4000	10.60	201.00
6000	7.80	239.00
8000	5.90	289.00
10000	4.40	350.00
12000	3.80	381.00

TJM STEALTH WINCH 15000
PN. 160-1331-01-0000

Single line rated pull 15000lbs single-line
Motor 12V 7.0hp, series wound
Control Wired & wireless remote included
Gear Train 3 stage planetary
Gear Reduction Ratio 261:1
Clutch Sliding ring gear
Braking Action Automatic in-the-drum
Drum Diameter/Length 3"/8.7"
Synthetic Rope 80ft of 7/16"
Fairlead Polished aluminium hawse fairlead
Battery Recommended 650CCA minimum for winching
Battery Leads 2 gauge
Finish Matte stealth black finish
Weight 65lbs
Overall Dimensions 23.25 x 6.75 x 7.5" (L x W x H)
Mounting Bolt Pattern 10 x 4.5"

FIRST LAYER OF DRUM*

*12volts constant load at winch motor

Line Load LBS	Line Speed FPM	Motor Amps
0	21.00	77.0
2000	14.40	134.00
4000	10.70	178.00
6000	8.53	234.00
8000	7.20	270.00
10000	6.60	320.00
12000	6.00	340.00
15000	3.90	425.00

STEALTH
SERIES PERFORMANCE WINCHES

